



TL-2000 Frequently Asked Questions (FAQ):

Question: What is TL-2000?

Answer: TL-2000 is an innovative asphalt rejuvenation black liquid material, which penetrates into the asphalt concrete and restores the elastic and plastic properties of road bitumen.

Question: Why choose TL-2000?

Answer: Due to the negative effects of UV rays and water, roads usually lose all their positive properties in 2-3 years after the road is built. TL-2000 can extend the service life of roads to 8-10 years or more, increases skid resistance, gives water and UV protection, and decreases considerably the road maintenance costs.

Question: Where has TL-2000 been used?

Answer: TL-2000 has been used and tested in over 30 countries including Israel, South Africa, China, Russia, Australia, Poland, Romania, Holland, USA, Hungary, Lithuania, Kazakhstan, Mexico and more.

Question: What is the material application rate per sq. meter?

Answer: The material application rate is dependent on the road condition, and may vary from 700 grams to 1.2 kg per square meter.

Question: How soon after applying TL-2000 can the road be re-opened for traffic?

Answer: TL-2000 takes approximately, depending on the ambient temperature, one hour to dry up, and then the road can be re-opened for traffic.

Question: How does HALIK distribute the TL-2000 material?

Answer: **We supply the KP (Key Product). Using 1 liter of KP and local components you can produce 20 kg of ready-to-use TL-2000 material that can coat approx. 20 sq. meters of road.**

Question: Where can I find more information on TL-2000 and other HALIK products?

Answer: You can find contact information and more information on TL-2000 and other HALIK products on the HALIK website at www.halik.biz

For answers to any other questions please don't hesitate to contact us at info@halik.biz